

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
1 December 2005 (01.12.2005)

PCT

(10) International Publication Number  
**WO 2005/114796 A1**

(51) International Patent Classification<sup>7</sup>: **H01R 13/629**

[KR/KR]; #104-1105, Mokdong Hyundae Apt., 1279, Sin-jeong-2-dong, Yangcheon-gu, Seoul 158-072 (KR).

(21) International Application Number:  
PCT/KR2005/001140

(74) Agent: **SUH, Won Ho**; 9th Fl., Seolim Bldg., 649-10, Youksam-Dong, Gangnam-Gu, Seoul 135-080 (KR).

(22) International Filing Date: 21 April 2005 (21.04.2005)

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language: Korean

(26) Publication Language: English

(30) Priority Data:  
10-2004-0027479 21 April 2004 (21.04.2004) KR

(71) Applicant (*for all designated States except US*): **SUNG KYUNG PRECISION CO., LTD.** [KR/KR]; #327-6, Dangeong-Dong, Namyang-Countryside, Kyunggi-Do 435-030 (KR).


(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

(72) Inventor; and


(75) Inventor/Applicant (*for US only*): **SUNG, Kyung Mo**

[Continued on next page]

(54) Title: FREE LOCK CONNECTOR



(57) Abstract: Disclosed herein is a connector for connecting a film wire to a substrate without a flip member. The connector comprises a housing with an insert hole formed therethrough, and a number of terminals inserted and fixed to the housing through the insert hole. Each terminal comprises a contact portion formed at one side thereof, and a seesaw member integrally formed at the other side thereof opposite to the contact portion via a central portion to seesaw about the central portion by a film wire when the film wire is inserted into the housing. The film wire is inserted into the housing with smaller force at an initial stage, and is fixed into the connector with a greater force at a final stage, so that a contact pin of the film wire can be inserted into a proper position without being damaged or scratched, and be stably fixed in the connector.





European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— *with international search report*